

IN THE CLAIMS

Please amend the claims as follows:

1 (Currently Amended). A data processor comprising:

a processor;

a first storage device; ~~and~~

a second storage device connected between said processor and said first storage device,

wherein, when a predetermined data required by said processor does not exist in said second storage device, a plurality of data corresponding to one line of said second storage device, including said predetermined data, are read from said first storage device and transferred to a certain line of said second storage device by burst transfer, and

wherein, when an interrupt request occurs during said burst transfer, said burst transfer is suspended and an interrupt processing is started; and

an information register stores information about a request for the predetermined data by said processor while said processor performs the interrupt processing, said information including information about a point at which said burst transfer is suspended.

2 (Previously Presented). The data processor according to claim 1, wherein said suspended burst transfer is restarted after the completion of said interrupt processing.

3 (Previously Presented). The data processor according to claim 2, wherein said suspended burst transfer is restarted only when returning to the original program in which said burst transfer is suspended.

4 (Previously Presented). The data processor according to claim 2, wherein  
when a plurality of interrupt requests occur, a plurality of interrupt processing are  
executed sequentially and, after the completion of the last interrupt processing, said  
suspended burst transfer is restarted.

5 (Currently Amended). The data processor according to claim 2, ~~further comprising:~~  
~~an information register for keeping information about a point at which said burst~~  
~~transfer is suspended,~~ wherein

among said plurality of data, only data not read from said first storage device due to  
suspension of said burst transfer are read from said first storage device and transferred based  
on said information when said burst transfer is restarted.

6 (Previously Presented). The data processor according to claim 2, wherein  
said second storage device has a plurality of lines,  
each line having information about a point at which said burst transfer is suspended,  
and

among said plurality of data, only data not read from said first storage device due to  
suspension of said burst transfer are read from said first storage device and transferred based  
on said information in said burst transfer restarted.

7 (Previously Presented). The data processor according to claim 1, wherein  
said suspended burst transfer is restarted when a certain line related to suspension of  
said burst transfer is accessed by said processor after said interrupt processing is completed.

8 (Currently Amended). The data processor according to claim 7, ~~further comprising:~~  
~~an information register for keeping information about a point at which said burst~~  
~~transfer is suspended,~~ wherein

among said plurality of data, only data not read from said first storage device due to suspension of said burst transfer are read from said first storage device and transferred based on said information in said restarted burst transfer.

9 (Previously Presented). The data processor according to claim 7, wherein  
said second storage device has a plurality of lines,  
each line having information about a point at which said burst transfer is suspended,  
and

among said plurality of data, only data not read from said first storage device due to suspension of said burst transfer are read from said first storage device and transferred based on said information in said restarted burst transfer.

10 (Previously Presented). The data processor according to claim 1, wherein  
said suspended burst transfer is restarted when an instruction for terminating said  
interrupt processing is detected during execution of said interrupt processing.

11 (Previously Presented). The data processor according to claim 10, wherein  
when a plurality of interrupt requests occur, a plurality of interrupt processing are  
executed sequentially and, when an instruction for terminating the last interrupt processing is  
detected, said burst transfer is restarted.

12 (Currently Amended). The data processor according to claim 10, ~~further comprising:~~

~~an information register for keeping information about a point at which said burst transfer is suspended,~~ wherein

among said plurality of data, only data not read from said first storage device due to suspension of said burst transfer are read from said first storage device and transferred based on said information in said restarted burst transfer.

13 (Previously Presented). The data processor according to claim 10, wherein  
said second storage device has a plurality of lines,  
each line having information about a point at which said burst transfer is suspended,  
and

among said plurality of data, only data not read from said first storage device due to suspension of said burst transfer are read from said first storage device and transferred based on said information in said restarted burst transfer.

14 (Original). The data processor according to claim 1, further comprising:  
a register to which a predetermined priority related to an interrupt factor is set, and  
a judgment unit comparing a priority of said interrupt request with said predetermined priority set in said register, and judging, from the comparison result, whether said burst transfer is suspended or not.

15 (Original). The data processor according to claim 1, further comprising:  
a register to which permission or non-permission to suspend said burst transfer is set for each interrupt factor,

wherein said burst transfer is suspended only when said interrupt request has an interrupt factor that is set so as to permit suspension of said burst transfer.

16 (Previously Presented). The data processor according to claim 1, wherein said interrupt request is executed after executing an instruction that is already fetched before an interrupt instruction corresponding to said interrupt request is fetched.

17. (Previously Presented) The data processor according to claim 1, wherein the processor processes instructions that are in a pipeline, the pipeline having an instruction fetch stage that fetches the instructions, a decode stage that decodes the instructions fetched by the instruction fetch stage, and an instruction execution stage that executes the instructions decoded by the decode stage, wherein

the processor performs an interrupt process when said interrupt request occurs, and first and second processes are selectively performed by the processor, in accordance with a priority of said interrupt request, as the interrupt process,

said first process including a process that causes said instruction execution stage to execute an interrupt instruction corresponding to said interrupt request after executing an instruction that is already fetched before the interrupt instruction is fetched by the instruction fetch stage, and

said second process including a process that causes said instruction execution stage to execute the interrupt instruction before executing an instruction that is already fetched before the interrupt instruction is fetched by the instruction fetch stage and that is not yet executed by the instruction execution stage.

18 (Original). The data processor according to claim 17, further comprising:

a register to which a predetermined priority is set, and  
a judgment unit comparing the priority of said interrupt request with the  
predetermined priority set in said register, and judging, from the comparison result, whether  
said first or second process is performed.

19 (Currently Amended). A data processor comprising:

a processor;

a first storage device; and

a second storage device connected between said processor and said first storage  
device,

wherein when a predetermined data required by said processor does not exist in  
said second storage device, a plurality of data corresponding to one line of said second  
storage device, including said predetermined data, are read from said first storage device and  
transferred to a certain line of said second storage device by burst transfer, and

when a first branch instruction is detected during a first burst transfer in the process  
of executing a first program, said first burst transfer is suspended and a second program,  
which is a branch target program, is executed,

said data processor further comprising ~~a register for keeping a first information  
about a point at which said first burst transfer is suspended,~~ an information register that stores  
information about a request for the predetermined data by said processor while said processor  
executes the second program, said information including information about a point at which  
said burst transfer is suspended, wherein

upon completion of execution of said second program, said first burst transfer  
suspended is restarted based on said first information.

20 (Previously Presented). The data processor according to claim 19, wherein,  
when a second branch instruction is detected during a second burst transfer in the  
process of executing said second program, said second burst transfer is suspended and a third  
program, which is another branch target program, is executed,  
said data processor further comprising another register for keeping a second  
information about a point at which said second burst transfer is suspended, wherein  
upon completion of execution of said third program, said suspended second burst  
transfer is restarted based on said second information.